

SKIMMER

FOR A SHINY POOL COMBINING FUNCTION AND DESIGN

Our skimmers made in Germany impress not only with their function but also their design and longevity from the use of high quality AISI 316 stainless steel as a raw material. The skimmer cleans the water surface, and with the floor drains, ensures ideal water circulation and perfect water quality in the pool. A large size strainer reliably catches dirt particles such as leaves, making skimmers an enormously important component of pool water treatment.

BEHNCKE offers compact models for small or cost-efficient pools, exclusive models with an integrated front slide-in strainer basket for comfortable pools and skimmers with extended installation depths for wide pool rims. If the client wants a high water level near the overflow pool, BEHNCKE's B500 Ultimate sets new standards for skimmers.



Always an idea ahead.



B100 / B200
Skimmer



STANDARD MODEL

Practical function with attractive pricing.

These skimmers have a simple and compact design, making them particularly suitable for small and cost-efficient pools.

B280 / B300 / B500 EVO / B600 EVO
Skimmer



WITH SLIDE-IN UNIT

Front slide-in unit for a flawless pool border.

With its large skimming opening and exclusive design, this skimmer is used especially in comfortable pools.

Its integrated front slide-in strainer basket eliminates the need for a service opening in the pool border.

B400
Skimmer



EXTENDED INSTALLATION DEPTH

The ideal solution for wide pool rims.

This skimmer is 30cm longer. It has an additional water chamber with a weld-in holder for installing a water level regulator.

B500 Slim / B600 Slim / B500 Ultimate
Skimmer



HIGH WATER LEVEL

New benchmark for water levels.

B500 Slim and B600 Slim enable high water levels in the pool. B500 Ultimate sets a new standard for water levels. The result? A water line that is very close to the overflow pool at maximum circulation output.

SPECIFICATIONS
Skimmer

Type	Skimmer type	Throughput	Connection size	Skimming width	Skimming height	Max. water level
B100	Standard	8–12m³/h	2"	200mm	142mm	100mm
B200	Standard	10–15m³/h	2"	200mm	142mm	100mm
B280	With slide-in unit	6–10m³/h	1 1/2"	200mm	145mm	85mm
B300	With slide-in unit	12–20m³/h	2"	300mm	217mm	100mm
B500 EVO	With slide-in unit	8–15m³/h	2"	454mm	285mm	55mm
B600 EVO	With slide-in unit	13–25m³/h	2"	665mm	85mm	55mm

Type	Skimmer type	Throughput	Connection size	Skimming width	Skimming height	Max. water level
B400	Extended installation depth	10–15m³/h	2"	200mm	145mm	100mm
B500 Slim	High water level	8–15m³/h	2"	454mm	85mm	55mm
B600 Slim	With slide-in unit	13–25 m³/h	2"	665mm	85mm	55mm
B500 Ultimate	High water level	7–14m³/h	2"	454mm	85mm	30 mm